

TECHNICAL DATASHEET

VenoPlank® 12+4mm and 15+5mm American Black Walnut Rustic



Product Details

Construction	Engineered
Top layer	±4mm or ± 5mm
Backing	WBP Exterior Birch ply
Profile	Tongue and Groove
Edge profile	Micro bevel long sides
Thickness	16mm and 20mm
Width	180, 200 and 220mm
Length	600mm → 3000mm
Grade	Rustic, see photo
Origin	Made In Holland
Janka Hardness	1,010 lbf (4,500 N)
Formaldehyde emission	E1
Certifications	FSC, CE (on request)
Reaction to fire	Dfl-s1
Thermal conduct.	12+4 mm: 0,100 m2 K/W 15+5 mm: 0,125 m2 K/W

Installation

Fully bonded	Yes, recommended
Floated	Yes
Floated on underlay	Yes
Over under floor heating	Yes, see Veno guidelines

Grading criteria:

- ✓ Sapwood allowed
- ✓ End check allowed
- ✓ Closed checks allowed
- ✓ Natural knots allowed
- ✓ Filled knots allowed
- ✓ Insect damages not allowed
- ✓ Filled side knots allowed
- ✓ All defects will be filled if possible
- ✓ Small open knot allowed
- ✓ Inner bark/rotten pieces will be brushed and scraped out before filling.

Tolerances

Width	+ and - max 0.1mm
Length	+ and - max 0.1mm
Thickness	+ and - max 0.5mm
Bowing / bend	Maximum ±16mm or ± 20mm