

TECHNICAL DATASHEET

VenoPlank® 15+5mm Rustic AB



Product Details

Construction	Engineered
Top layer	±5mm
Backing	WBP Exterior Birch ply
Profile	Tongue and Groove
Edge profile	Micro bevel long sides
Thickness	20mm
Width	180, 220 and 260mm
Length	1800 → 2470mm Max. 10% shorter
Grade	Rustic AB, see photo
Origin	Made In Holland
Janka Hardness	1,120 lbf (4,980N)
Formaldehyde emission	E1
Certifications	FSC, CE (on request)
Reaction to fire	Dfl-s1
Thermal conduct.	0,122 m2 K/W

Installation

Fully bonded	Yes, recommended
Floated	Yes
Floated on underlay	Yes
Over under floor heating	Yes, see Veno guidelines

Grading criteria:

- ✓ **A trace of heart on the face side allowed**
- ✓ **No sapwood**
- ✓ **Small end check allowed**
- ✓ **Small closed checks allowed**
- ✓ **Natural knots allowed up to 60mm**
- ✓ **Filled knots allowed up to 30mm**
- ✓ **Insect damages not allowed**
- ✓ **Rouge not allowed**
- ✓ **Filled side knots allowed**
- ✓ **No inner bark allowed**
- ✓ **All defects will be filled if possible**

Tolerances

Width	+ and - max 0.1mm
Length	+ and - max 0.1mm
Thickness	+ and - max 0.5mm
Bowing / bend	Maximum ±20mm